

Recommendation for use	In polyolefins, the dosage levels for EVERNOX-B401 and EVERNOX-B401GF are between 0.1% to 0.25%, depending on polymers and processing conditions. The optimum level is various of application specific needs.
Handling & Safety	EVERNOX-B401 and EVERNOX-B401GF should be handled with care and prevent contamination of the environment. Avoid dust formation and ignition sources. For more detailed information please refer to the material safety data sheet.
Packing	The following packages are available upon customer's request : (1) 20 kgs×2 PE bags in the carton box. (2) 25 kgs×2 PE bags in the carton box. (3) 50 kgs fiber drum. (4) Other specific request.
Transportation	EVERNOX-B401 and EVERNOX-B401GF are not dangerous materials according to the transportation regulations.
Storage	EVERNOX-B401 and EVERNOX-B401GF should be stored under suitable conditions (dry & cool). Maximum recommended storage temperature under 45°C and the storage time from the date of analysis : 24 months.



妙春實業股份有限公司
EVERSPRING CHEMICAL CO., LTD.
 台中市工業區 24 路 4 號
 4, 24th Road, Industrial Park, Taichung, Taiwan
 Tel : +886-4-23592448 Fax : +886-4-23593163
 E-mail : sales@everspringchem.com.tw
 Web site : www.everspringchem.com